


Series E-i

Reverse-Osmosis Systems with integrated ion-exchange cartridge for cost-effective on-site production of demineralized water

System benefits at a glance:

- Cost-effective and safe on-site production of demineralized water
- Compact aluminum housing
- Internal storage tank 8 liters (gross volume)
- Integrated conductivity controller for monitoring of the production process
- Ideally suited for the automatic supply of sterilizers with an increased demand for demineralized water at all degrees of feed water hardness
- Including faucet (white)
- Operates only with water pressure (no electricity required)
- **eco**-models with water-saving technology



Saving water with the **eco-module**:

- The **eco-module** maintains a constant ratio of permeate to waste-water throughout the whole storage tank filling process
- This allows waste-water savings up to 70% compared to conventional water purification systems with reverse osmosis technology
- For clarification: with a demand of 20 liters demineralized water per day the **eco-module** will be able to save approx. 30.000 liters waste-water per year
- Additional benefits of the **eco-module**: Higher permeate purity, faster filling of the storage tank and additionally lower strain on pre-filters, membrane and ion-exchange cartridges

Additional system benefits:

- Reverse-osmosis technology is able to remove bacteria, viruses, chlorine, hardness components, heavy metals, nitrate, medical residue, pesticides etc. reliable and ecological without using any chemicals
- All used materials, pressure tubing and components are food safe
- Customized adaptations and versions are possible
- Long service life of all cartridges enables a low service effort
- Incl. detailed manual (installation, operation, disinfection, service and trouble-shooting guide)

Series E-i

TECHNICAL DATA

VEWAMED® WATER-PURIFICATION-SYSTEM	
Production capacity:	VEWAMED E50i and E50i-eco: approx. 8 liters/hour (190 liters/day) (Specifications are standard values at 3,4 bar water pressure and a water temperature of 25°C without tank backpressure)
Conductivity controller:	Integrated conductivity controller for monitoring of the production process (checks conductivity of the demineralized water and the permeate with the press of a button)
Filtration stages:	Stage 1: Inline carbon filter cartridge VOC1-10 Stage 2: Inline sediment filter cartridge VOSF5-10 with 5 µm filtration Stage 3: TFC-membrane VDF50 with a rejection rate of approx. 95% Stage 4: 2 pcs. Inline ion-exchange cartridge VOIO-10 with high capacity
Service life ion-exchange cartridges:	Approx. 300 days at 5 liters of demineralized water per day, tap water at 14°dH and permeate at 40 µS/cm (extract from service life chart)
Service life pre-filters:	12 months (depending on sediment pollution)
Service life membrane:	Approx. 5 years (depending on feed water quality resp. feed water hardness)
Efficiency (system recovery):	Optimally set to approx. 1:1 - 1:3 (ratio of permeate to waste-water)
Tube connectors:	John Guest push-fit connectors
Tubing:	John Guest
System housing:	Aluminum (powder-coated white)
Additional system components:	High quality components from leading brand manufacturers
Certified system quality:	System comes with a unique serial number and test report
System configuration:	Optimal system configuration allows for a fast and easy service
User manual:	Installation, operation, disinfection, service
System dimensions (w x h x d):	21,5 x 37,5 x 46,5 cm
Storage tank:	Internal storage tank 8 liters (gross volume)
System weight E50i:	Approx. 10,0 kg (including packaging)
System weight E50i-eco:	Approx. 10,5 kg (including packaging)
Scope of delivery:	System with storage tank 8 liters, faucet, installation-kit and user manual
OPERATING CONDITIONS	
Feed water pressure:	2,8 to 7,0 bar
Feed water hardness range:	All degrees of hardness: 1 (soft) to 4 (very hard)
Feed water temperature:	4,0°C to 38,0°C
MODELS	DESCRIPTION / PART NUMBER
VEWAMED Series E-i:	E50i / 11528 E50i-eco / 11529
VEWAMED Series E-i (with integrated pressure regulator):	E50i / 11508 E50i-eco / 11509
CONSUMABLES	DESCRIPTION / PART NUMBER
VEWAMED E50i and E50i-eco:	Filterset WS4 / 20314 Membrane VDF50 / 20161
OPTIONAL ACCESSORIES	DESCRIPTION / PART NUMBER
Water shut-off valve:	Water shut-off valve LD1 / 30133
Stainless steel faucet:	Faucet stainless steel SE4QSS/ 50103
Additional accessories, spare parts and disinfectant:	Look at VEWAMED® price list

VEWAMED®
Water-Purification-Systems

VEWAMED GmbH & Co. KG
Warter Str. 20
D-72224 Ebhausen
Tel: +49 (0) 7458 / 5110142
info@vewamed.de
https://vewamed.de

Submitted by: